

XP-002276757

AN - 1994-073195 [09]

AP - SU19915021629 19911210

CPY - SHEI-I

DC - Q79

FS - GMPI

IC - F42B12/34 ; F42B30/02

IN - KORNEEVA N A; KORNEICHEV I P; SHEININ S M

PA - (SHEI-I) SHEININ S M

PN - RU2002201 C1 19931030 DW199409 F42B30/02 005pp

PR - SU19915021629 19911210

XIC - F42B-012/34 ; F42B-030/02

XP - N1994-057112

AB - RU2002201 The bullet consists of a lead casing with external threads and is connected by a screw (4) to the plastic tail stabiliser which is fitted with an obturation cuff (8). Within the tail section of the casing, there is a circular boring (6) with a cylindrical guiding surface with a corresponding guiding element (12) on the stabiliser.

- When fired, the bullet hits the target without having been distorted. Because of the braking effect of the head of the bullet, the threads on the casing shear, allowing the tail section to move forwards. The tail surface (11) hits the casing surface (10) and forces it outwards thus increasing the area of the bullet and also its destructive effect.

- ADVANTAGE - Increase in effectiveness and destructive effect.

Bul.39-40/30.10.93

- (Dwg.3/5)

IW - BULLET SMOOTH BORE HUNTING WEAPON FIT CIRCULAR GUTTER SIDE STABILISED

IKW - BULLET SMOOTH BORE HUNTING WEAPON FIT CIRCULAR GUTTER SIDE STABILISED

INW - KORNEEVA N A; KORNEICHEV I P; SHEININ S M

NC - 001

OPD - 1991-12-10

ORD - 1993-10-30

PAW - (SHEI-I) SHEININ S M

TI - Bullet for smooth-bore hunting weapon - fitted with circular guttering on same side as stabiliser